

# Trendsetter VLF

## Trendsetter VLF Quantum

semi-automatic very large-format CTP



**Reliability, productivity, and consistency in very large-format CTP**



The robust, highly-productive Trendsetter® VLF family of thermal CTP off-set platesetters offers semi-automatic or fully automatic operation, stability, easy maintenance, and superior imaging quality. Available in five sizes and several speeds, and featuring a versatile Autoloader option, Trendsetter VLF devices are optimized for the special requirements of very large-format book, catalog and directory printers—as well as packaging converters and trade shops. Reliability and consistent quality have made Trendsetter VLF platesetters the most widely used very large-format CTP devices in the industry.

### Trendsetter VLF / Trendsetter VLF Quantum Product Specifications

	4557	5067	5080	5467	5880
<b>Performance</b>					
<b>Imaging time*</b>					
<b>Standard speed</b>	162.6 mm (6.4 in) per minute	162.6 mm (6.4 in) per minute	162.6 mm (6.4 in) per minute	139.7 mm (5.5 in) per minute	139.7 mm (5.5 in) per minute
<b>Fast speed</b>	243.8 mm (9.6 in) per minute	243.8 mm (9.6 in) per minute	243.8 mm (9.6 in) per minute	213.4 mm (8.4 in) per minute	213.4 mm (8.4 in) per minute
<b>Very Fast speed</b>	688.3 mm (27.1 in) per minute	688.3 mm (27.1 in) per minute	688.3 mm (27.1 in) per minute	614.7 mm (24.2 in) per minute	614.7 mm (24.2 in) per minute
<b>Throughput**</b>					
<b>Standard speed</b>	6 plates per hour	5 plates per hour	4 plates per hour	4 plates per hour	4 plates per hour
<b>Fast speed</b>	8 plates per hour	7 plates per hour	6 plates per hour	6 plates per hour	5 plates per hour
<b>Very Fast speed</b>	17 plates per hour	15 plates per hour	13 plates per hour	14 plates per hour	12 plates per hour

\* Based on maximum media size. Depends on media sensitivity.

\*\* Based on 90 seconds of non-imaging time plus 30 seconds for operator plate handling. Maximum media size. Depends on media type.

# Trendsetter VLF / Trendsetter VLF Quantum Product Specifications

	4557	5067	5080	5467	5880
<b>Imaging Specifications</b>					
<b>Workflow connectivity</b>	Creo Brisque™ or Brisque™ Pack workflow Creo Prinerly® or Prinerly <i>Powerpack</i> ™ workflow Third-party connectivity				
<b>Resolution</b>	1200 or 2400 dpi				
<b>Screening</b>					
<b>Trendsetter VLF</b>	200 lpi maximum linescreen				
<b>Trendsetter VLF Quantum</b>	450 lpi maximum linescreen Staccato 20 (Option: Staccato 10)				
<b>Image area</b>					
<b>around the drum circumference</b>	508 to 1,130 mm (20 to 44.46 in)	508 to 1,257 mm (20 to 49.46 in)	508 to 1,257 mm (20 to 49.46 in)	508 to 1,359 mm (20 to 53.46 in)	508 to 1,460 mm (20 to 57.46 in)
<b>along the drum axis</b>	394 to 1,448 mm (15.5 to 57 in)	394 to 1,702 mm (15.5 to 67 in)	394 to 2,032 mm (15.5 to 80 in)	394 to 1,702 mm (15.5 to 67 in)	394 to 2,032 mm (15.5 to 80 in)
<b>Media Specifications</b>					
<b>Media type</b>	Thermal IR-sensitive aluminum plate, 830 nm Thermal IR-sensitive film, 830 nm				
<b>Plate sizes</b>					
<b>min. to max., around drum x along drum</b>	508 x 394 mm (20 in x 15.5 in) to 1,143 x 1,448 mm (45 x 57 in)	508 x 394 mm (20 in x 15.5 in) to 1,270 x 1,702 mm (50 x 67 in)	508 x 394 mm (20 in x 15.5 in) to 1,280 x 2,032 mm (50 x 80 in)	508 x 394 mm (20 in x 15.5 in) to 1,372 x 1,702 mm (54 x 67 in)	508 x 394 mm (20 in x 15.5 in) to 1,473 x 2,032 mm (58 x 80 in)
<b>Media thickness</b>	<ul style="list-style-type: none"> <li>plates: 0.15 to 0.40 mm (6 to 16 mil)</li> <li>film: 0.18 mm (7 mil) minimum</li> </ul>				
<b>Physical Characteristics</b>					
<b>Size (H x W x D)</b>	<ul style="list-style-type: none"> <li>housing: 1,168 x 3,124 x 1,803 mm (46 x 123 x 71 in)</li> <li>height to top of load ramp: 1,575 mm (62 in)</li> </ul>				

# Let's Talk

Contact your Creo representative to find out more about Creo digital prepress solutions, and to select the Trendsetter VLF device and options that best serve your current and future business needs.

## About Creo

Creo Inc. is a global company with key strengths in imaging and software technology. As the leading provider of prepress systems, Creo helps over 25,000 customers worldwide adopt digital production methods that reduce costs,

increase print quality, and allow them to serve their customers more efficiently. Based in Vancouver, Canada, Creo reported fiscal 2004 revenue of US\$635.8 million. Creo trades on NASDAQ (CREO) and the TSX (CRE).

© 2004 Creo Inc. The products mentioned in this document are trademarks or service marks of Creo Inc. and may be registered in certain jurisdictions. Other company and brand, product and service names are for identification purposes only and may be trademarks or registered trademarks of their respective holders. Data subject to change without notice.

Produced using Creo technology

**creo**<sup>™</sup>

[www.creo.com](http://www.creo.com)

#### Creo Inc.

3700 Gilmore Way  
Burnaby, British Columbia  
Canada V5G 4M1  
T. +1.604.451.2700  
F. +1.604.437.9891

#### Creo Americas, Inc.

3 Federal Street  
Billerica, MA 01821  
USA  
T. +1.978.439.7000  
F. +1.978.439.7031

#### Creo Asia Pacific Ltd.

3/F 625 King's Road  
North Point  
Hong Kong  
T. +852.2882.1011  
F. +852.2881.8897

#### Creo EMEA, SA.

Waterloo Office Park  
Drève Richelle 161  
B-1410 Waterloo  
Belgium  
T. +32.2.352.2511  
F. +32.2.351.0915

#### Creo IL Ltd.

P.O. Box 330  
Herzlia Industrial Park  
46103 Herzlia B  
Israel  
T. +972.9.959.7222  
F. +972.9.950.2922

#### Creo Japan Inc.

1-17-8, Higashi-Ikebukuro  
Toshima-ku, Tokyo  
170-0013  
Japan  
T. +81.3.5954.9050  
F. +81.3.5954.9055

## ***NEW SOFTWARE AVAILABLE***

To find out more about using the Harlequin® RIP-Kit software with this particular output device visit [rti-rips.com](http://rti-rips.com) or call 800-816-5755 (International Callers: 941-925-1303)

[rti-rips.com](http://rti-rips.com) **800-816-5755**

RTI Global, Inc.  
United States  
Phone: 800-816-5755 or 941-925-1303  
Fax: 941-924-0699  
Email: [sales@rti-rips.com](mailto:sales@rti-rips.com)  
Website: [www.rti-rips.com](http://www.rti-rips.com)

The following information is provided for documentation purposes only. All trademarks property of their respective owners.