

DPX 2[®]

Creating new standards for the B3 (2-up) print segment with Polyester CTP

The **DPX 2** is the perfect choice for a B3 (2-up) printer. It provides all the benefits you need to grow your business. It is fully automated and will be running unattended for hours, while providing press ready plates. Superior quality plates which fits right on to your press. The DPX 2 is simply the next step to your success.

- The ECRM DPX 2 offers you two different plate sizes online at the same time, a great flexibility saving you time and money.
- Maintenance friendly design - built-in processor is a twin-bath processor with one temperature controlled activator tank with circulation pump - requires little attention and gives you more time for your core business, printing.
- Even with the built-in processor the footprint of the DPX 2 is only 138.0 mm by 102.0 mm (54.3" x 40.1")
- Integrated register punches for both 220 mm and 425 mm distance. Ensures perfect fit on press and saves endless time of press adjustment.
- Simple and intuitive operator interface makes daily use of the DPX 2 easy.
- Low installation cost - ECRM DPX 2 does not require a water supply or drainage.
- DPX 2 can be connected to any common front-end. Regardless of your workflow – we have the solution for you.
- High precision imaging - automatic and dynamic adjustment of the spot size resulting in a perfect spot that gives you high quality prints.



Choose ECRM for your Polyester CTP solutions

ECRM products offer the lowest total cost of ownership in the business and the highest quality performance in the industry. Our manufacturing facility is located in Tewksbury, Massachusetts, USA and is certified as being in conformity to ISO 9001:2000 standards. Our signature flexible design lets you decide what's best for your CTP system, workflow, plates and processors. We support you every step of the way and work with you to ensure complete system integrity.



DPX 2 Specifications

| | |
|-----------------------------|---|
| Plate Sizes | Max: 420 mm x 550 mm (16.1" x 21.6") Upgraded Max.: 460 mm x 550 mm (18.1" x 21.6") Min: 250 mm x 250 mm (10" x 10") |
| Plate Thickness | 0.1 mm - 0.2 mm (0.004" - 0.008") |
| Media Types | Red light sensitive Digital Silver Halide Polyester |
| Recording Source | Optic fiber 650-675nm Red Laser |
| Resolutions | Resolutions from 900 to 3600 dpi |
| Maximum Line Screen | Max 175lpi Tint: 3-97% Tint variation over full exposure: ± 1 dot % |
| Repeatability | Image repeatability: 25 µm / 0.001" over 4 plates Punch register Absolute: ± 0.5 mm / ±0.02" Relative: ± 25 µm / ±0.001" |
| Processing | Integrated, fully computer controlled processor and dryer. |
| Environmental | Power: 200 - 240VAC, 50/60Hz, 13A |
| Operating Conditions | 25-80% humidity, non-condensing Temperature 18 - 28 °C / 65 - 82 °F |
| Weight | 410 kg (902 lbs.) |
| Footprint Dimensions | Length: 138 cm (54.3") Width: 102 cm (40.1") Height: 107 cm (42.1") |

ECRM®
imaging systems

Headquarters:

554 Clark Road
Tewksbury, MA 01876
USA
Tel: (+1) 978.851.0207
Fax: (+1) 978.851.7016
sales@ecrm.com
www.ecrm.com

International Sales Offices:

| | |
|--|---|
| 3 Century Court, Tolpits Lane Watford, Hertfordshire WD18 9PU, UK Tel: (+44) 1923.218.255 Fax: (+44) 1923.218.256 sales_uk@ecrm.com | B2, 10/F, Block B, Kailey Industrial Centre, 12 Fung Yip Street, Chai Wan, Hong Kong Tel: (+852) 2564-8989 Fax: (+852) 2564-8821 sales_hk@ecrm.com sales_asia@ecrm.com |
|--|---|

All ECRM products carry the CE mark. All products are CSA & CSA/NRTL Certified. Class 1 Laser Products ECRM's Tewksbury facility is ISO 9001:2000 certified.

All trademarks are the property of their respective owners and their use in this documentation is acknowledged and recognized. The information provided in this document is subject to change without notice.

NEW SOFTWARE AVAILABLE

To find out more about using the Harlequin® RIP-Kit software with this particular output device visit rti-rips.com or call 800-816-5755 (International Callers: 941-925-1303)

rti-rips.com **800-816-5755**

RTI Global, Inc.
United States
Phone: 800-816-5755 or 941-925-1303
Fax: 941-924-0699
Email: sales@rti-rips.com
Website: www.rti-rips.com

The following information is provided for documentation purposes only. All trademarks property of their respective owners.